

Aluminum Cladding Awning



These windows feature structural assembly, an inclined one-piece sill, weatherstripping, and sealed glass to ensure their quality, resistance, and superior energy efficiency. Their handy opening systems ensure effective ventilation and ease of care. Awning windows open out from the bottom using an adjustable lever system. This opening method offers excellent ventilation throughout the home, even when it's raining.

With aluminum and PVC blending, these windows offered a variety of arrangements possibilities and a wide selection of colors for exterior cladding.

OPTIONS

Frames

- 130 mm x 130 mm (5 1/8" x 5 1/8")
- 130 mm x 159 mm (5 1/8" x 6 1/4")
- 184 mm x 184 mm (7 1/4" x 7 1/4")

Wood

- Pine or Douglas fir

Glass and spacers

- Double glazed
- Triple glazed

Brickmoulds

- Extruded aluminum
- Number 9933, 9923, V-17227 or S-2544 (color selection)

Grills

- Removable pine or Douglas fir with PVC cladding on half
- Integrated

Divided lights

- Simulated divided lights
 - 20 mm (3/4")
 - 32 mm (1 1/4")



TECHNICAL SPECIFICATIONS

Frame

130 mm (5 1/8") frame
159 mm (6 1/4") sill

Structural assembly

Sealed sill and side joints

- 1 One-piece sill, inclined 6°

Premium quality solid wood, kiln dried and treated with a special preservative

- 2 Extruded aluminum brickmould

- 3 Extruded aluminum exterior cladding

Sash

- 4 Weatherstripping on openings

90° opening

Fixed sash insulated with adhesive polyurethane foam

Glass

- 5 Energy efficient double glazed glass with 13 mm (1/2") air space

Screen

- 6 Bronze aluminum frame with fiberglass screen (optional white, black, cashmere, oil rub bronze and satin nickel)

Hardware

Truth hardware's *ENCORE* line with retractable bronze handle (optional white, black, cashmere, oil rub bronze and satin nickel)

Lock mechanism : Multi-point

